

US006263984B1

(12) United States Patent

Buckman, Sr.

(10) Patent No.: US 6,263,984 B1

(45) **Date of Patent:** Jul. 24, 2001

(54) METHOD AND APPARATUS FOR JET DRILLING DRAINHOLES FROM WELLS

(76) Inventor: William G. Buckman, Sr., 504

Memphis Junction Rd., Bowling Green,

KY (US) 42101

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/480,170

(22) Filed: Jan. 10, 2000

Related U.S. Application Data

(60) Provisional application No. 60/143,316, filed on Jul. 12, 1999, and provisional application No. 60/120,731, filed on Feb. 18, 1999.

(51) Int. (Cl. ⁷		E21B	7/18
-------------	------------------	--	------	------

(52) **U.S. Cl.** 175/67; 175/45; 175/424

(56) References Cited

U.S. PATENT DOCUMENTS

1,865,853	7/1932	Granville .
3,130,786	4/1964	Brown et al
3,145,776	8/1964	Pittman .
3,191,697	6/1965	Haines .
3,234,723	2/1966	Brown .
3,853,185	12/1974	Dahl et al
3,924,698	12/1975	Juvkam-Wold .
3,960,407	6/1976	Noren .
4,050,529	9/1977	Tagirov et al
4,119,160	10/1978	Summers et al
4,134,453	1/1979	Love et al
4,317,492	3/1982	Summers et al
4,346,761	8/1982	Skinner et al
4,368,786	1/1983	Cousins .
4,497,381	2/1985	Dickinson, III et al.
4,533,182	8/1985	Richards .
4,640,362	2/1987	Schellstede .

4,821,961	4/1989	Shook .
4,826,087 *	5/1989	Chinery 239/551
4,848,486	7/1989	Bodine .
4,852,668	8/1989	Dickinson, III et al
4,896,733 *	1/1990	Baker et al
4,957,173	9/1990	Kinnan .
5,113,953	5/1992	Noble .
5,148,877	9/1992	MacGregor .
5,148,880	9/1992	Lee et al

(List continued on next page.)

OTHER PUBLICATIONS

"The Leader in High-Pressure Water Jet Technology" NCLB Corp Water jetting Nozzle Catalog., pp. 1–3, 62–63 (Jan. 1998).

Mauer, "Novel Drilling Techniques", Pergamon Press, pp. 38–45 & 96–97 (1968).

D. A. Summers, et al., Diajet Use in an Environmental Application, pp. 1–10 was presented to the 11th International Conference on Jet Cutting Technology, St. Andrews, Scotland, (Sep. 8–10, 1992).

Pendleton, et al., "Bechtel develops innovative method for horizontal drilling" *Technology Oil & Gas Journal* pp. 95–99, (May 27, 1985).

Primary Examiner—Frank Tsay (74) Attorney, Agent, or Firm—Baker Botts L.L.P.

(57) ABSTRACT

Nozzle jet drill bits for drilling drainholes from a wellbore are provided in a 4 ½-inch or larger casing. The drills are small enough to allow use of a bit diverter to turn the bits about 90 degrees in the casing when attached to an elastomeric high-pressure tube. Pumping of fluid, which may contain abrasive particles, through the bits allows drilling though the wall of casing, if present, and continued drilling into a formation surrounding the well without withdrawing the bit from the well. Direction-indicating instruments and geophones may be used to measure or monitor direction and location of the bit. One type of jet drill that may be used can change direction of drilling by controlling pressure at the bit.

23 Claims, 3 Drawing Sheets

